



# **EZ2LOAD** MCU2500

Reliable and adaptable delivery system

**The Power  
of Partnership**





# MCU2500 Quick Facts

- Engineered for reliability
- Easy to use and maintain
- Inherently safe system
- High capacity pumping system
- Designed for development and downhole loading
- Remotely operated

## Features

### Size

55 in. (1.4 m) L 37 in. (1.0 m) W 58 1/4 in. (1.5 m) H

### Empty Weight

770 lbs (350 kg) approx.

### Product Tank Capacity

2,500 lbs (1,130 kg) approx.

### Water Tank Capacity

34 gal (128 l)

### Pump Rate and Pressure

275 lbs/min (130 kg/min)\* @ 230 psi (16 bar)

### Controls

Pneumatic remote control

### Options

Wireless remote control

Preset Counter

Pump flow rate and totalizer

Gasser compatible


## Requirements

### Pneumatic

115 psi 8 (bar) @ 45 cfm (1,275 lpm) 1 in. (25 mm) inlet

### Electrical

12 vdc @ 5 amps



Rendering is an example, and because of Orica's continuous improvement program, actual product will be confirmed with Orica at time of purchase.

# EZ2LOAD MCU 2500

EZ2LOAD is the product name for Orica's new MCU2500 series of delivery systems. EZ2LOAD consists of two types of pumps that introduce Orica's bulk products in underground or surface mining. There are two available models in the series, the MCU2500 and MCU2550. The MCU2500 is a self-contained delivery system while the modular MCU2550 is a tankless delivery system that is adaptable to most existing IBC containers and DOT approved tanks

For more information on this and other products, please email [OMSNorthAmerica@orica.com](mailto:OMSNorthAmerica@orica.com) or call the Beloeil Equipment Center at 1-877-446-8818.

## Benefits

- **Engineered for Reliability:** Simple design does not require an external drive motor to operate like other piston or progressive cavity pumps. All that is needed to operate the pump is an air source.
- **Easy to Use & Maintain:** Maintenance is simplified and easy. There are fewer moving components to break down and parts are easily accessible.
- **Inherently Safe System:** If there is a problem with the pump, it will shut down. The pump will go up to 230 psi (16 bar) and automatically shuts off. No need for the installation of safety devices and has no external moving parts that could potentially injure operators.
- **Easy Transportation:** Designed to allow easy transportation to a loading area by using either a forklift, easily mounted on a mine carrier for underground mining or a surface vehicle.
- **High Delivery Pumping System**
- **Designed for Development and Downhole Loading**
- **Remotely Operated**

## Features

Size	55 in. (1.4 m) L 37 in. (1.0 m) W 58 ¼ in. (1.5 m) H
Empty Weight	770 lbs (350 kg) <i>approx.</i>
Tank Capacity	2,500 lbs (1,130 kg) <i>approx.</i>
Pumping Pressure	Up to 230 psi (16 bar)
Pump Flow Rate	275 lbs/min (125 kg/min)*
Controls	Pneumatic remote Control Local on/off
Options	Wireless remote control Preset counter Pump flow rate and totalizer Gasser compatible

\* All weights are Based on a product density of 1.25g/cc

## Requirements

Pneumatic	115 psi (8 bar) @ 45 cfm (1,275 lpm) 1 in. (25 mm) inlet
Electrical	12 vdc @ 5 amps**

\*\* Required only for electrical option

**Orica Canada Inc**  
**2151 Mtée St Jean Baptiste**  
**St Mathieu-de-Beloeil, Quebec J3G 4S5**  
**Phone 1-877-446-8818**  
**[www.oricaminingservices.com](http://www.oricaminingservices.com)**  
**[omsnorthamerica@orica.com](mailto:omsnorthamerica@orica.com)**

The Orica name and logo are trademarks of Orica Group Companies. The information contained herein is based on experience and is believed to be accurate and up to date as at the date of its preparation. However, uses and conditions of use are not within the manufacturer's control and users should determine the suitability of such products and methods of use for their purposes. Neither the manufacturer nor the seller makes any warranty of any kind, express or implied, statutory or otherwise, except that the products described herein shall conform to the manufacturer's or seller's specifications. The manufacturer and the seller expressly disclaim all other warranties, INCLUDING, WITHOUT LIMITATION, WARRANTIES CONCERNING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Under no circumstances shall the manufacturer or the seller be liable for indirect, special, consequential, or incidental damages including, without limitation, damages for lost or anticipated profits.