


Dynadet™-C2-0ms Sweden



Description

The instantaneous electric detonator Dynadet™-C2-0ms serves to initiate commercial explosives.

The detonators are delivered with an attached connecting sleeve for simple and safe coupling. The insulation on the detonator leads is made of polyethylene providing good resistance against friction and cutting damage while being environmentally friendly.

Application

Dynadet™-C2-0ms is used for the initiation of commercial explosives in quarrying and construction works.

Recommendations for Use

- Not to be used in a gaseous environment or where there is danger of coal dust explosion.
- Use without primer and without pneumatic Anfo pre-loading only when loading boreholes with explosives of type PAC.
- Can alternatively be manufactured with continuously insulated wires.
- To prevent the possibility of detonating cord tail cut off when using detonating cord and Orica Dynadet™-C2 electric detonators the following tie up method is recommended.

Roll the starter tail of detonating cord into a loop approx. 20 cm in diameter and secure with shot firing tape. Secure and tape the electric detonator inside the loop with the detonator facing the taped joint and in the direction of the detonating cord connected to the shot.



Technical Properties

Product	Dynadet™-C2-0ms
Shell	Aluminium
Primary Charge	Lead Azide
Base Charge	PETN
Output strength	REF. DET. #3
Delay intervals	0
Delay time (ms)	0
Type of sensitivity	Class 2 (U)
No-fire-impulse (mJ/ Ω)	≤8
All-fire-impulse (mJ/ Ω)	≥16
No-fire-current (A)	≤0.45
All-fire current (A)	≥1.5
Max. hydrostatic pressure	3 bar / 7 days
Wire	
Insulation	PE
Wire colour	yellow / white
Wire type	Steel
Wire diameter (mm)	0.70
Insulation diameter (mm)	1.60 ±0.05
Tensile strength (N)	min. 125
Pull-out strength (N)*	min. 40
Wire ends	Fixed connecting sleeve
Wire length (m)	4

*Testing according to EN13763.7

Packaging

Dynadet™-C2-0ms electric detonators are available in the following packaging:

1.4S

Wire length	Total Resistance	No. of detonators per bag	No. of detonators per box	Gross weight per box kg	Net weight per box kg	Net explosive weight per box kg
4 (Fe)	2.9 ±0.4	10	200	12.2	8.8	0.188

Other lengths are maybe available upon request. Please contact your local Orica representative for further information.

Dynadet™-C2-0ms Sweden

Storage and Handling

Product Classification

Authorised Name: Dynadet™-C2-0ms
Proper Shipping Name: Detonators, electric
UN No.: 0456
Class Code: 1.4S
EC Type Certificate: 0589.EXP.2782/18

Dynadet™-C2-0ms should be stored in a suitably licensed magazine for Class 1.4S explosives.

Detonators are best stored at ambient temperatures of 0 °C to 40 °C.

Dynadet™-C2-0ms have a storage life of 2 years in stable, temperate conditions.

Dynadet™-C2-0ms may be used at temperatures from -25 °C to a maximum of 50 °C. If your application requires you to operate outside this temperature range please contact your local Orica Account Manager.

Disposal

Disposal of explosives materials can be hazardous. Methods for safe disposal of explosives may vary depending on the user's situation. Please contact a local Orica representative for information on safe practices.

Safety

Always follow requirements for protection against hazardous electrical sources when using Dynadet™-C2-0ms detonators. Care should be taken not to cause initiation by intense impact, friction or heat.

Training

This Technical Data Sheet is for information only. Electric detonators should only be used by personnel who have been properly trained to use this system.

Disclaimer

© 2018 Orica Group. All rights reserved. All information contained in this document is provided for informational purposes only and is subject to change without notice. Since the Orica Group cannot anticipate or control the conditions under which this information and its products may be used, each user should review the information in the specific context of the intended application. To the maximum extent permitted by law, the Orica Group specifically disclaims all warranties express or implied in law, including accuracy, non infringement, and implied warranties of merchantability or fitness for a particular purpose. The Orica Group specifically disclaims, and will not be responsible for, any liability or damages resulting from the use or reliance upon the information in this document.

The word Orica and the Ring device are trademarks of the Orica Group.

Orica Sweden AB
Gyttorp
713 82 Nora
Sweden
Phone: +46 587 85000
Fax: +46 587 25345
Email: info.gyse@orica.com

Emergency Telephone Number

Within Sweden: +46 20 850001
Outside Sweden: contact local representative